

COMPACT HMS 200



Compact HMS 200 is a global award winning innovation utilising world class technology. The remote controlled HMS 200 provides the operator with increased capability, safety and productivity.

Hetronic Remote Control

Encased in a tough, IP65, fiber enforced polycarbonate case, the lightweight, ergonomic radio remote control by HMS Equipment, is rugged and reliable; engineered for the toughest industrial environments.

Offering increased safety, productivity and operational efficiency, the new mini loader with remote control uses patented User Interface (UI) technology for optimal control and reliability. New, fully proportional, electro-hydraulic valves deliver precise and repeatable movement under all working conditions.

*Actual products may vary in design and in use. We reserve the right to improve our products and change our specifications without notice. The gross horsepower of the engine has been laboratory rated by the manufacturer. Actual engine horsepower may be lower due to operating requirements.

KEY FEATURES

Low Profile

- With a height of only 625mm, the mini loader is capable of working in most hard to access areas.

Proximity Detection System

- Alerts the operator when they are too close to the machine to prevent accidents.
- Shuts down the machine when operator is too close to the machine.

Hetronic Remote Control

- Self-test routine.
Emergency stop switch.
- Joysticks spring return to neutral.





COMPACT HMS 200

ENGINE	20HP Kubota D902, 3 cylinder, liquid cooled, diesel
FUEL TANK CAPACITY	20 Litres
HYDRAULIC TANK CAPACITY	115 Litres
SYSTEM PRESSURE	240 Bar
DIMENSION	Length: 2660mm (w/bucket) Height: 625mm Width: 1320mm
GROUND CLEARANCE	74mm
SPEED	Low speed: 2.5kph High speed: 5kph
WEIGHT	1720kg
BUCKET CAPACITY	Vol: 0.155m ³ Mass: 375kg

HETRONIC RADIO REMOTE CONTROL

FREQUENCY RANGE	434MHz
RF POWER	10 mW standard
MODULATION	FM – Narrow band
BANDWIDTH	25kHz
TYPICAL RANGE	100m standard, 200m with optional antenna
TEMPERATURE RANGE	-25°C – 70°C
HUMIDITY RANGE	0 – 97%
RESPONSE TIME	Approx. 55ms
TRANSMITTER	IP65, built-in antenna, 12hrs continuous operation, spring return joystick
RECEIVER	IP65
BATTERY & CHARGER	Charger Power: 9 – 30 VDC, 110/220 VAC Charging Time: <4hrs Battery Life: Approx. 900 charges Battery Type: NiMh Battery Capacity: 1200mAH
CERTIFICATES	RCM, CE, TUV, SUVA, ISO 9001 & compliance with AS/NZS 4240.1:2009